

# SLIM LAUNCH LEAD



IP 66

Up to 1.000 m

Extremely light and compact body



# SLIM LAUNCH LEAD

Supplied within a highly resistant case, FIBERNET slim launch lead is light, compact and easy to carry. Conguration up to 1.000 m of ber connectorized with most common connectors.



## TECHNICAL SPECIFICATIONS

|                              |                                   |                                                   |
|------------------------------|-----------------------------------|---------------------------------------------------|
| DIMENSIONS                   | 230 x 175 x 53 mm                 |                                                   |
| WEIGHT                       | 0,6 kg                            |                                                   |
| INSERTION LOSS PER CONNECTOR | < 0,25 dB                         |                                                   |
| RETURN LOSS                  | UPC < -50 dB / APC < -60 dB       |                                                   |
| FIBER LENGHT                 | Up to 1.000 m                     |                                                   |
| MATERIAL                     | Polypropylene                     |                                                   |
| TYPE OF FIBER                | SM                                | G.652.D. / G.657.A1 - A2<br>G.655 NZD / SMF - 28e |
|                              | MM                                | OM1 / OM2 / OM3 / OM4                             |
| TYPE OF CONNECTORS           | SC / LC / MU / FC<br>/ ST / E2000 | SC / LC / FC /<br>E2000                           |
| FERULE FINISHING             | UPC                               | APC                                               |

\*Customizable with customer logo